

# H650 Speed

## Product Description

### Features

H650 Speed is a rapid drying and hardening self levelling and smoothing compound specifically designed for areas where speed is essential for rapid renovation and repair work prior to using Bona R850 Speed. It's special properties are:

- Ultra Rapid Drying, could be covered after app. 1 hour,
- Exceptionally fluid, applicable in a thickness from 1,5 to 10 mm\*, for bigger thickness the material could be spun out
- High strength and hardness
- Low shrinkage
- Complete crystallized binding of water (hydration).
- \*Installing wood floor using R850 Speed is only recommended after 1 hour when the thickness of the levelling compound does not exceed: 5 mm

### Technical Data

Base: Cement, art. Resins

Colour: Grey

Consumption: 1.5 kg/(m<sup>2</sup> mm)

Pot life: 15 min

First load (walking): after approx. 1 hours

Covering: after approx. 1 hours

GISCODE: ZP1, Chrom (VI) reduced < 2 ppm

Cleaning agent: Water (only for fresh product!)

Storage: not below 5 °C during Winter, below 30 °C in Summer

Shelf life: 6 months

Pack Size: 25 kg paper sacks (40 per pallet)

### Safety

Contains Portland Cement. Irritates eyes and skin. Keep away from children. Avoid contact with eyes and skin. By contact with eye flush with much water, consult physician. Wear protection gloves.

Additional detailed information is noted in the appropriate Safety Data Sheet.

