



Bona R845

Product Description

Features

R845 is an elastic; according to EN 14293 (soft); 1-component silane based adhesive for dimensional stable multilayered, engineered parquet. Tensions to the sub floor are reduced. The use of a primer is in general not necessary. The adhesive hardens by a chemical reaction with moisture.

- 1-component, easy to handle
- soft elastic
- Water and solvent free, nearly no swelling of the wood
- Good adhesion to almost all substrates and timber materials, splashed material can be easily removed
- Firm texture – retains trowel pattern
- Rapid initial bonding strength

Technical Data

Base:	Silane modified-Prepolymere
Colour:	cream
Viscosity:	Easy to apply - stable
Density:	1.6 g/cm ³
GISCODE:	RS 10
Cleaning agent:	S100, acetone and ethanol. Hardened adhesive can only be moved mechanically.
Application of load:	24 to 48 h
Surface treatment:	Depending on air humidity and the moisture content of the materials between 2 and 4 days.
Storage / transport:	The temperature must not fall below +5°C or exceed +25°C during storage and transport. Store in a cool, dry, well ventilated place.
Shelf life:	6 months.
Pack size:	24 kg (32 per pallet) and 15 kg (44 per pallet)

Site Work is described in an additional data sheet.

Bona takes only responsibility for the delivered product, no responsibility can be taken for the total installed product. If in doubt, conduct a test or a trial. Observe also other Bona product datasheets.

Safety

Additional detailed information is noted in the appropriate Safety Data Sheet.