

## Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 07.04.2009

Revision: 12.03.2009

### 1 Identification of the substance/preparation and of the company/undertaking

#### Product details

**Trade name:** 3262 Osmo Polyx-Oil Rapid, matt

**Application of the substance / the preparation**

Paint

**Manufacturer/Supplier:**

Osmo Holz und Color GmbH & Co. KG  
Affhüppen Esch 12  
D-48231 Warendorf

**Further information obtainable from:**

Product safety department  
Phone: +49 (0) 251 / 692 - 188  
Fax: +49 (0) 251 / 692 - 462  
e-mail: helmut.starp@osmo.de

**Information in case of emergency:**

emergency phone no. Berlin (24h): +49 (0) 30 / 19240

### 2 Hazards identification

**Hazard description:** Not applicable.

**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.  
R 10 Flammable.

**Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

### 3 Composition/information on ingredients

#### Chemical characterization

**Description:** Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

CAS: 64742-48-9 EINECS: 265-150-3	Naphtha (petroleum), hydrotreated heavy	Xn; R 65-66	25-50%
CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light	Xn; R 10-65-66-67	10-25%
CAS: 34590-94-8 EINECS: 252-104-2	(2-methoxymethylethoxy)propanol		2.5-10%
CAS: 136-52-7 EINECS: 205-250-6	cobalt carboxylate	Xi, N; R 38-43-51/53	≤1%

**Additional information:**

For the wording of the listed risk phrases refer to section 16.

(Contd. on page 2)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 07.04.2009

Revision: 12.03.2009

**Trade name: 3262 Osmo Polyx-Oil Rapid, matt**

(Contd. of page 1)

#### 4 First aid measures

<b>General information:</b>	Immediately remove any clothing soiled by the product. Take affected persons out into the fresh air.
<b>After inhalation:</b>	Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
<b>After skin contact:</b>	Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.
<b>After eye contact:</b>	Rinse opened eye for several minutes under running water. Then consult a doctor.
<b>After swallowing:</b>	If swallowed, seek medical advice immediately and show this container or label.
<b>Information for doctor:</b>	
<b>The following symptoms may occur:</b>	Headache Dizziness

#### 5 Fire-fighting measures

<b>Suitable extinguishing agents:</b>	CO <sub>2</sub> , powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
<b>For safety reasons unsuitable extinguishing agents:</b>	Water with full jet
<b>Special hazards caused by the substance, its products of combustion or resulting gases:</b>	Formation of toxic gases is possible during heating or in case of fire.
<b>Protective equipment:</b>	Mouth respiratory protective device.
<b>Additional information</b>	Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Cool endangered receptacles with water spray.

#### 6 Accidental release measures

<b>Person-related safety precautions:</b>	Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources. Ensure adequate ventilation
<b>Measures for environmental protection:</b>	Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system.
<b>Measures for cleaning/collecting:</b>	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders). Warm water and cleansing agent
<b>Additional information:</b>	See Section 13 for disposal information.

(Contd. on page 3)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 07.04.2009

Revision: 12.03.2009

**Trade name: 3262 Osmo Polyx-Oil Rapid, matt**

(Contd. of page 2)

### 7 Handling and storage

**Handling:**

**Information for safe handling:** Keep away from heat and direct sunlight.  
Keep receptacles tightly sealed.  
Use only in well ventilated areas.  
Prevent formation of aerosols.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

**Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool location.  
Store only in the original receptacle.

**Information about storage in one common storage facility:**

Do not store together with alkalis (caustic solutions).  
Do not store together with oxidizing and acidic materials.

**Further information about storage conditions:**

Keep container tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.

### 8 Exposure controls/personal protection

**Additional information about design of technical facilities:**

No further data; see item 7.

**Ingredients with limit values that require monitoring at the workplace:****64742-49-0 Naphtha (petroleum), hydrotreated light**

TWA (8 H)	Short-term value: 1000 mg/m <sup>3</sup> Source UK SIA
-----------	---

**34590-94-8 (2-methoxymethylethoxy)propanol**

WEL	Long-term value: 308 mg/m <sup>3</sup> , 50 ppm Sk
-----	---

**Additional information:**

The lists valid during the making were used as basis.

**Personal protective equipment:****General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing  
Keep away from foodstuffs, beverages and feed.  
Avoid contact with the eyes and skin.  
Do not eat, drink, smoke or sniff while working.  
Do not carry product impregnated cleaning cloths in trouser pockets.

(Contd. on page 4)

**Safety Data Sheet**  
according to 1907/2006/EC, Article 31

Printing date 07.04.2009

Revision: 12.03.2009

**Trade name: 3262 Osmo Polyx-Oil Rapid, matt**

(Contd. of page 3)

<b>Respiratory protection:</b>	Use suitable respiratory protective device only when aerosol or mist is formed. Not necessary if room is well-ventilated.
<b>Protection of hands:</b>	Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
<b>Material of gloves</b>	Nitrile rubber, NBR
<b>Penetration time of glove material</b>	The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
<b>For the permanent contact gloves made of the following materials are suitable:</b>	Nitrile rubber, NBR
<b>As protection from splashes gloves made of the following materials are suitable:</b>	Nitrile rubber, NBR
<b>Eye protection:</b>	Tightly sealed goggles
<b>Body protection:</b>	Protective work clothing

**9 Physical and chemical properties****General Information**

<b>Form:</b>	Fluid
<b>Colour:</b>	Yellowish
<b>Odour:</b>	Mild

**Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	> 144°C

**Flash point:** 35°C**Ignition temperature:** 240°C**Self-igniting:** Product is not selfigniting.**Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**Explosion limits:**

<b>Lower:</b>	0.6 Vol %
<b>Upper:</b>	7.0 Vol %

**Vapour pressure at 20°C:** 10 hPa**Density at 20°C:** 0.9 - 1.0 g/cm<sup>3</sup> (DIN 51757)

(Contd. on page 5)

**Safety Data Sheet**  
 according to 1907/2006/EC, Article 31

Printing date 07.04.2009

Revision: 12.03.2009

**Trade name: 3262 Osmo Polyx-Oil Rapid, matt**

(Contd. of page 4)

<b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
<b>Viscosity:</b> <b>Kinematic at 20°C:</b>	>81 s (DIN 53211/4)
<b>Solvent content:</b> <b>VOC (EC)</b>	< 500 g/l (VOC-max. = 500 g/l (2010 A/i))

### 10 Stability and reactivity

**Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**Dangerous reactions**

Reacts with fabric soaked in the product (e.g. cleaning wool).

Self igniting.

Exothermic reaction.

Forms heat.

**Dangerous decomposition products:**

Carbon monoxide and carbon dioxide

Nitrogen oxides (NO<sub>x</sub>)

**Additional information:**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

### 11 Toxicological information

**Acute toxicity:**

**LD/LC50 values relevant for classification:**

**64742-48-9 Naphtha (petroleum), hydrotreated heavy**

Oral LD50 &gt;2000 mg/kg (rat)

Dermal LD50 &gt;2000 mg/kg (rat)

Inhalative LC50 / 4h &gt;5 mg/l (rat)

**64742-49-0 Naphtha (petroleum), hydrotreated light**

Oral LD50 &gt;2000 mg/kg (rat)

Dermal LD50 &gt;2000 mg/kg (rat)

Inhalative LC50 / 4h &gt;20 mg/l (rat)

**96-29-7 2-butanonoxime**

Oral LD50 3700 mg/kg (rat)

Dermal LD50 200-2000 mg/kg (rat)

(Contd. on page 6)

**Safety Data Sheet**  
 according to 1907/2006/EC, Article 31

Printing date 07.04.2009

Revision: 12.03.2009

**Trade name: 3262 Osmo Polyx-Oil Rapid, matt**

(Contd. of page 5)

Inhalative	LC50 / 4h	20 mg/l (rat)
------------	-----------	---------------

**Primary irritant effect:**

**on the skin:** At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

**on the eye:** Irritating effect.

**Sensitization:** No sensitizing effects known.

### 12 Ecological information

**Ecotoxicological effects:****Acquatic toxicity:****64742-48-9 Naphtha (petroleum), hydrotreated heavy**

EC50 / 48h	>1000 mg/l (daphnia)
------------	----------------------

IC50 / 72h	>1000 mg/l (algae)
------------	--------------------

LC50 / 96h	>1000 mg/l (fish)
------------	-------------------

**64742-49-0 Naphtha (petroleum), hydrotreated light**

EC50 / 24h	<130 mg/kg (Oncorhynchus mykiss (Regenbogenforelle))
------------	--

	>100 mg/kg (selenastrum capricornutum)
--	--

**General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

### 13 Disposal considerations

**Product:**

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**European waste catalogue**

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
----------	---

15 01 10	packaging containing residues of or contaminated by dangerous substances
----------	--

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

**Recommended cleansing agents:** Solvent naphtha

### 14 Transport information

**Land transport ADR/RID (cross-border)**

**ADR/RID class:** 3 Flammable liquids.

(Contd. on page 7)

**Safety Data Sheet**  
 according to 1907/2006/EC, Article 31

Printing date 07.04.2009

Revision: 12.03.2009

**Trade name: 3262 Osmo Polyx-Oil Rapid, matt**

(Contd. of page 6)

<b>Danger code (Kemler):</b>	30
<b>UN-Number:</b>	1263
<b>Packaging group:</b>	III
<b>Hazard label:</b>	3
<b>Description of goods:</b>	1263 PAINT

<b>Maritime transport IMDG:</b>	
<b>IMDG Class:</b>	3
<b>UN Number:</b>	1263
<b>Label</b>	3
<b>Packaging group:</b>	III
<b>EMS Number:</b>	F-E,S-E
<b>Marine pollutant:</b>	No
<b>Proper shipping name:</b>	PAINT

<b>Air transport ICAO-TI and IATA-DGR:</b>	
<b>ICAO/IATA Class:</b>	3
<b>UN/ID Number:</b>	1263
<b>Label</b>	3
<b>Packaging group:</b>	III
<b>Proper shipping name:</b>	PAINT

### 15 Regulatory information

**Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

**Risk phrases:**

10 Flammable.

**Safety phrases:**

- 2 Keep out of the reach of children.
- 16 Keep away from sources of ignition - No smoking.
- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

**Special labelling of certain preparations:**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

Contains 2-butanonoxime, cobalt carboxylate. May produce an allergic reaction.

Safety data sheet available for professional user on request.

(Contd. on page 8)

**Safety Data Sheet**  
*according to 1907/2006/EC, Article 31*

Printing date 07.04.2009

Revision: 12.03.2009

**Trade name: 3262 Osmo Polyx-Oil Rapid, matt**

(Contd. of page 7)

**National regulations:****GISBAU-Code**

GISCODE: Ö60

**VOC (EC)**

&lt; 500 g/l (VOC-max. = 500 g/l (2010 A/i))

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Department issuing MSDS:** product safety department**Contact:** Hr. Dr. Starp**\* Data compared to the previous version altered.**